




FOR PROFESSIONAL USE ONLY

Quick Ref:	GreaseBuster AS Degreaser
-------------------	----------------------------------

  	Solventborne. Wipe on, Wipe off. Use clean cloths, changing frequently	<p>Description: Solvent blend specially formulated to degrease and clean bare metal surfaces and old paint coatings. The target use for this product is refinishing and refurbish of existing vehicles and the painting of newly build commercial vehicles and trailers. The EU VOC limit for this product (product category: IIB.A) in ready to use form is max 850 g/litre. The VOC content of this product in ready to use form is max 780 g/litre</p>
	CONSULT TECHNICAL DATA SHEET BEFORE USE	<p>Surface Preparation: GreaseBuster AS Degreaser serves as a degreaser while at the same time neutralising static charge. A surface with a static charge can attract electrically neutral objects. If an object has a static charge when being painted, this may increase dust level. Objects made of plastics in particular can build up a high static charge by friction.</p>
	Wear suitable protection	<p>Degreasing and condensation on metal surfaces:</p> <p>After a surface has been cleaned and degreased, the solvent will evaporate. The heat needed for evaporation is withdrawn from that surface, making it colder than the surrounding atmosphere, which results in condensation (often not visible) on the surface. Allow the moisture sufficient time to evaporate. The first coat of paint can be applied as soon as the surface has regained the temperature of the surrounding atmosphere. Earlier application of the coating may lead to adhesion problems. The same problem may arise if a vehicle is transferred from a cold room to a warm one or from outdoors to indoors. Allow vehicles a minimum of one hour to acclimatise.</p>
		<p>Application process: Wet a clean cloth with GreaseBuster AS Degreaser and use it to clean the surface under treatment. Immediately thereafter, wipe the surface dry with clean dry cloths. After this treatment, the surface will be free of contaminants and static charge.</p> <p>Note: Replace cloths being used for degreasing and cleaning regularly with clean ones. Always segregate solvent contaminated waste, (fire risk).</p>
		<p>Packaging: 5L can</p>
	<p>HEALTH & SAFETY DATA concerning GreaseBuster AS Degreaser</p> <p>For professional use only (see Material Safety Data Sheet) See text on the label of this product. The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.</p>	

FOR PROFESSIONAL USE ONLY**AkzoNobel Coatings LTD, Car Refinishes****Address:** 136 Milton Park, Abingdon
Oxfordshire OX14 4SB**Tel:** 44 (0)1235 862226**AkzoNobel CR Ireland****Address:** Avonbeg Industrial Estate
Long Mile Road, Dublin 12**Tel:** 00 353 (0)1450 1344**FOR PROFESSIONAL USE ONLY**

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head OfficeAkzoNobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.masonct.com